

## SAM<sup>TM</sup> Data Sheet SAM-1064-55-10ps-x, $\lambda$ = 1064 nm

Laser wavelength  $\lambda = 1064 \text{ nm}$ 

High reflection band  $\lambda = 1010 ... 1110 \text{ nm}$ 

Absorbance  $A_0 = 55 \%$  Modulation depth  $\Delta R = 40 \%$  Non-saturable loss  $A_{ns} = 15 \%$ 

Saturation fluence  $\Phi_{sat} = 35 \,\mu\text{J/cm}^2$ 

Relaxation time constant  $\tau \sim 10 \text{ ps}$ 

Damage threshold  $\Phi = 600 \,\mu\text{J/cm}^2$ 

Chip area 4.0 mm x 4.0 mm; other dimensions on request

Chip thickness 450 µm

Protection the SAM is protected with a dielectric front layer

Mounting option  $\mathbf{x}$  denotes the type of mounting as follows:

 $\mathbf{x} = 0$  unmounted

 $x = 12.7 \, \mathrm{g}$ glued on a copper heat sink with 12.7 mm  $\varnothing$  $x = 25.4 \, \mathrm{g}$ glued on a copper heat sink with 25.4 mm  $\varnothing$  $x = 12.7 \, \mathrm{s}$ soldered on a copper heat sink with 12.7 mm  $\varnothing$  $x = 25.4 \, \mathrm{s}$ soldered on a copper heat sink with 25.4 mm  $\varnothing$ 

x = 25.0 w soldered on a water cooled copper heat sink with 25.0 mm ∅ x = FC mounted on a 1 m single mode fiber with FC connector

## Low intensity spectral reflectance and dispersion coefficient D<sub>2</sub>

